

ALLNET Meetingraum RGB LED Tablet 10 Zoll RK3576 Android 16 und NFC/RFID Farbe schwarz

>>> [Zum Shop-Artikel](#)



EAN CODE



NFC Detail:

Item	Type	Tested
1	ISO/IEC 18092(NFCIP-1)	yes
2	ISO/IEC 21481(NFCIP-2)	yes
3	ISO/IEC 14443A	yes
4	ISO/IEC 14443B	yes
5	ISO/IEC 15693	yes
6	Mifare Classic	yes
7	Mifare Ultralight	yes
8	MIFARE DESFire EV1/ EV2	yes
9	Sony FeliCa	yes
System	CPU	RK3576S Quad core cortex A53+Quad core cortex A72
	RAM	4GB
	Internal memory	32GB
	Operation system	Android 16

		Touch screen			10-Point capacitive touch
Display	Panel				10.1"LCD panel
	Panel Type				IPS
	Resolution				1280*800
	Display Colors				16.7M Colors
	Viewing angle				R/L 85/85, U/D 85/85
	Display mode				Normally black
	Contrast ratio				1500:1
	Response Time				25ms
	Back-light Type				ELed
	Luminance				280cd/m2
	Aspect Ratio				,16:10
Network	WiFi				IEEE 802.11a/b/g/n/ac/ax
	Buletooth				Bluetooth 5.4
	Ethernet				10M/100M/1000M ethernet
Interface	SIM Slot				4G Flow Card
	SD Slot				SD card ,Max support to 64GB
	Earphone				3.5mm earphone + Microphone
	USB				USB 3.0 host
	USB				USB for serial (TTL Level) ,Optional USB Host
	RJ45				Ethernet interface
	Type-C				Only supports ADB function
	Power jack				DC power input

Media play	Video format			MPEG-1,MPEG-2,MPEG-4, H.265,H.264,VP9,AV1, AVS2 ,MVC,AVC ,etc., support up to 4K
	Audio format			MP3/WMA/AAC/WAV/OGG, etc
	Photo			JPEG/PNG/GIF,etc
Other	Product Colors			White/Black
	VESA			75*75 mm
	Button			Power
	G-sensor			Support 90 degrees
	Speaker			2*2W
	Microphone			Single microphone
	NFC			Optional,13.56 MHz,ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic encrypted tags and cards
	RFID			Optional ,125k,ISO/IEC 11784/11785, EM4100,TK4100/GK4100
LED light bar			LED light bar with RGB and mixed color	

	Camera				Routine angle 5.0MP with mipi
	4G Moduel				Optional
	Language				Multi-language
	Certificates				CCC/CE/FCC
	POE				Support IEEE8 02.3at, up to 30W
Working Surrounding	Working Temperature				0°C---40°C
	Storage Temperature				-20°C---60°C
	Working Humidity				20~80%RH
	Storage Humidity				10~95%RH
Accessories	Adapter				Adapter, 12V/1. 5A
	User manual				*1

Merkmale

Merkmal	Wert
Abmessung:	259.36 x 278.36 x 28
Alternative Betriebssysteme:	Linux;
Arbeitsspeicher (RAM):	4
Auflösung Panel:	1280x800
Betriebssystem:	Android 16
Bluetooth:	ja
Chipset:	RK3576
Diagonale:	10
Einsatzbereiche:	Indoor
Farbe Displayrand:	schwarz
Farbe Gehäuse:	schwarz;
Hauptspeicher:	32
IP Schutzklasse Display:	IP 20
Kamera:	ja



Art.-Nr.: 256880
Herst.-Nr.: MeetTwo-101B

Merkmal	Wert
Mobilfunk:	nein
Montageart:	integrierte Halterung;
NFC&RFID:	13,56MHz
Produktart:	Tablet
Stromversorgung:	PoE&Netzteil
Touchscreen:	kapazitiv
WLAN:	2,4&5
Gewicht:	1,418 Kg
Garantie:	24.00 Monate