

Datenblatt Art. 919.284

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

PRCD Adapter

Elektrische Kenngrößen Electrical parameters

Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50Hz	Frequency	50Hz
Anschlussleistung	3680W	Connected load	3680W

Netzanschluss Power supply

Stecker	CEE 7/7 (Type E/F)	Plug	CEE 7/7 (Type E/F)
----------------	---------------------------	-------------	---------------------------

Stromausgang Power output

Steckdosen	Socket outlets
1x CEE 7/3 (Type F)	1x CEE 7/3 (Type F)
2-polig mit Schutzkontakt	2-pole with earthing contact
Mit erhöhtem Berührungsschutz	With shutter
weiß, mit Klappdeckel,	white, with hinged lid,
16A / 250V~, IP44	16A / 250V~, IP44

Schutzeinrichtungen Protective devices

PRCD	PRCD
ohne Schutzleiterüberwachung	without protective conductor monitoring
Abschaltung 2-polig (L, N)	2-pole interrupt (L, N)
mit Unterspannungsauslösung	with undervoltage tripping
Auslösestrom < 30mA	Tripping current < 30mA
Auslösezeit < 30mS	Tripping time < 30mS

Weitere Produkteigenschaften Further product attributes

Material	Material
Gehäuse:	Housing:
PA6 GF30 850°C, weiß	PA6 GF30 850°C, weiß

Lieferumfang	Scope of delivery
1x PRCD Adapter	1x PRCD Adapter
in Blisterverpackung	in blister packaging

Umgebungsbedingungen Environmental conditions

Schutzart	IP44	Protection type	IP44
------------------	------	------------------------	------

Konformität / Approbation**Conformity / Approval****geprüft nach:**EN 61008-
1:1994+A2+A11, EN
61008 2-1/ 08.94
IEC884-1 A1/ 12.94**Tested in accordance with:**EN 61008-
1:1994+A2+A11, EN
61008 2-1/ 08.94
IEC884-1 A1/ 12.94

