



NOTE:  
RoHS 2.0 & Reach COMPLIANT

Insertion Loss (dB)	≤ 0.20
Operating Temperature (° C)	-40 ~ +80
Storage Temperature (° C)	-40 ~ +85

**MATERIAL LIST:**

⑥	LC Erika violett Plastic body RAL4003(SC simplex footprint)	1pcs	
⑤	LC Sleeve <b>ceramic</b> (Multi-Mode)	1pcs	
④	Erika violett bush RAL4003	2pcs	
③	LC Erika violett Plastic body RAL4003 (SC simplex footprint)	1pcs	
②	LC Metal Mount	1pcs	
①	LC White Dust Cap	4pcs	

Chart:

NO.	ITEM NO.	EAN Number
1	S215482	4038816140654

NO.	SPECIFICATION STANDARD	QT' Y	REMARK
	NEW	2017-4-25	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE

SYNERGY 21						
CUSTOMER				ITEM NO.	See the chart	
PRODUCT NAME	LC MM Erika violett(ceramic)Duplex Plastic Adapter(SC SX Footprint) w/o flange	manufacture country	CHINA	UNIT	MM	
DRAWNBY	CHECKBY	APPOBY	DATE			
SYNERGY 21	SYNERGY 21	SYNERGY 21	2017-4-25			