


ALLNET Switch full managed 48 Port Gigabit / 48x LAN / 4x SFP+ / 19" / "ALL-SG8652M-10G"

>>> [Go to the shop article](#)



EAN CODE



ALLNET Switch full managed 48 Port Gigabit / 24x LAN / 4x SFP+ / 19" / "ALL-SG8652M-10G"

Highlights:

- 48 ports Gigabit Layer2+ switch architecture (ports 1~48).
- 4 ports SFP+ 10G slots compatible for optional GBICs (ports 48~52).
- Support L2+ Switching features including 802.1Q VLAN, Mirroring, Port isolation, IGMP Snooping, DHCP Snooping, LLDP, IP Source Guard, ARP inspection, ACLs etc.
- Support spanning tree STP(802.1D) and RSTP(802.1W) and MSTP(802.1s).
- Support enhanced management through WEB, CLI, TELNET, SSH, SNMP.
- Support cable diagnosis and SFP DDM.
- Support PoE management, like PoE schedule, PoE PD-alive.
- Support G.8032 quick ring protocol. Self-recovery time <20ms.
- Support DDM, SFP digital diagnostics monitoring
- Support IPV4 and IPV6 static routing functions
- Support memory and CPU monitoring
- 4KV surge protection, 6KV contact/8KV air protection
- 19" angle or wall/table mounting possible

Full L2+ managed Ethernet aggregation /core fiber switch with 48* 10/100/1000M RJ45 ports and 4*1/10G SFP+ fiber slot ports, Built-in 60W power supply. Support 1U/19 inch rack installation.

ALL-SG8652M-10G is an aggregation /core fiber switch with 48* 10/100/1000M RJ45 ports and 4*1/10G SFP+ fiber slot ports, Built-in 60W power supply. Support 1U/19 inch rack installation. With full L2 management


functions, such as VLAN, QoS, ACL, IPv4/IPv6 routing, ALL-SG8652M-10G can be used in various applications, such as video surveillance, VoIP, wireless coverage etc with a affordable cost.

10Gbps Uplink Capacity for Big Bandwidth Application

10G Ethernet is a big leap in the evolution of Ethernet. The 10G SFP+ slots support dual-speed 10GBASE-SR/LR or 1000BASE-SX/LX, meaning the administrator now can flexibly choose the suitable SFP/SFP+ transceiver according to the transmission distance or the transmission speed required to extend the network efficiently. It is a cost-effective solution for SMB network to achieve the maximum performance of the 10G networks

Solution for IPv6 Networking

With the IPv6/IPv4 dual stack and other management functions, ALL-SG8652M-10G is the best choice for IP CCTV surveillance, VoIP and wireless solution providers to develop the IPv6 network. Meanwhile the fiber switch help the SMBs to upgrade their network infrastructures to the IPv6 era without any extra investment.



Robust Layer 2 Features

ALL-SG8652M-10G can be programmed for advanced Ethernet switch management functions, such as port aggregation, Q-in-Q VLAN, Spanning Tree Protocol, QoS, bandwidth control, ERPS IGMP/MLD snooping etc. ALL-SG8652M-10G allows the operation of a high-speed trunk combining multiple ports.

Powerful Security Functions

ALL-SG8652M-10G provides a comprehensive access control list (ACL) for enforcing security to the edge. It can be used to restrict to network access by denying packets based on source and destination IP address, TCP/UDP port number or defined typical network applications. Its protection mechanism also comprises 802.1x Port-based and MAC-based user and device authentication. With the private VLAN function, communication between edge ports can be prevented to ensure user privacy.

Enhanced Security and Traffic Control

ALL-SG8652M-10G supports DHCP Snooping, IP Source Guard and Dynamic ARP Inspection functions to prevent IP snooping from attack and discard ARP packets with invalid MAC address. The network administrator

can now construct highly-secure corporate networks with considerably less time and effort than before.


User-friendly Secure Management

For efficient management, ALL-SG8652M-10G managed switch series is equipped with console, web and SNMP management interfaces. With management interface, ALL-SG8652M-10G offers an easy-to-use, platform independent management and configuration facility. ALL-SG8652M-10G supports SNMP and it can be managed via any management software based on the standard SNMP v1 or v2 Protocol. Meanwhile ALL-SG8652M-10G offers Cisco-like command via Telnet or console port and customer doesn't need to learn new command from these switches. Moreover, ALL-SG8652M-10G offers the remotely secure management by supporting SSH, SSL and SNMP v3 connection where the packet content can be encrypted at each session.

Intelligent SFP DDM Function

ALL-SG8652M-10G supports SFP-DDM (Digital Diagnostic Monitor) function that greatly helps network administrator to easily monitor real-time parameters of the SFP and SFP+ transceivers, such as optical output power, optical input power, temperature, laser bias current, and transceiver supply voltage.

Digital Diagnostic Monitor (DDM)




Fast Recovery Redundant Ring for Critical Network Applications

The ALL-SG8652M-10G supports redundant ring technology and features strong, rapid self-recovery capability to prevent interruptions and external intrusions. It incorporates advanced ITU-T G.8032 ERPS technology, Spanning Tree Protocol (802.1s MSTP), and redundant power input system into customer's industrial automation network

to enhance system reliability and uptime in harsh factory environments. In a certain simple Ring network, the recovery time of data link can be as fast as 20ms.

ERPS Ring for Video Transmission Redundancy



Technische Daten:

Model	ALL-SG8652M-10G
Copper Ports	48-10/100/1000BASE-T RJ45 auto-MDI/MDI-X ports
Fiber Ports	4x1G/10GBASE-X SFP interfaces, supports 1G/10Gbps dual mode
Console Ports	1 x RS-232-to-RJ45 serial port (115200, 8, N, 1)
Switch Architecture	Store-and-Forward
Switch Fabric	176 Gbps/non-blocking
Throughput	130.94Mpps @64 bytes
Address Table	32K entries



Share Data Buffer	32Mb
Jumbo Frame	9600 Bytes
SDRAM	2Gb
Flash Memory	128Mb
Flow Control	IEEE 802.3x pause frame for full-duplex Back pressure for half-duplex
Reset Button	>2 sec.: Factory default and reset
Power Supply	100~240V AC, 50/60Hz, 4A (max.)
Power Consumption	Max. 370 watts
LED Indicators	Power: Green Solid on- power work normal, off- power disconnected System: Green Blink-work normally, solid on- soft work abnormal, fast blink- soft upgrade 10/100/1000T RJ45 Interfaces (Port 1 to Port 48): 1000 LNK/ACT (Green),10/100 LNK/ACT (yellow), Blink- port connected with data transmission; Solid on- port connected without data transmission 1G/10G SFP Interfaces (Port 49 to Port 52): Blue Blink- port connected with data transmission; Solid on- port connected without data transmission
EMC	Surge Immunity: 4KV Per: IEC61000-4-5 ESD Protection: ESD Level 4 Per: IEC61000-4-2 EFT Level 4 Per: IEC61000-4-4
Layer2 Functions	
Port configuration	Auto-negotiation Flow Control Port Mirror: TX/RX/BOTH; Many-to-1 monitor

	CPU Mirror
	Traffic statistics
Link Aggregation	Static link aggregation LACP (Dynamic Trunk/Static Trunk) Algorithm based on Source/Destination MAC Algorithm based on Source/Destination IP
MAC Table	Aging Time Static MAC address Dynamic MAC address management
VLAN	4094 Active VLANs 4094 VID 802.1Q Tag VLAN Port VLAN Protocol VLAN MAC VLAN Voice VLAN 802.1ad Q-in-Q tunneling Private VLAN (Protected port) GARP/GVRP
ACL	512ACLs L2, L3 e L4 Time-based ACL IP ACL MAC ACL MAC-IP ACL User-Defined ACL ICMPv6
Spanning tree	802.1D Spanning Tree Protocol (STP) 802.1w Rapid Spanning Tree Protocol (RSTP) 802.1s Multiple Spanning Tree Protocol (MSTP) Loop Guard Root Guard TC-BPDU Guard BPDU Guard



	BPDU Filter
Ring Protection	<20ms G.8032 ERPS Ring Fast Ring
Multicast	1024 groups IGMP v1/v2/v3 Snooping, Fast Leave MLD Snooping Multicast VLAN IGMP filter MVR Multicast Routing
QOS	8 mapping IDs to 8 level priority queues CoS port-based CoS 802.1p-based CoS DSCP-based Scheduling algorithms SP, WRR, SP+WRR Storm Control (Broadcast, Multicast, Unknown Unicast) Bandwidth control per port SWRR, DWRR for Scheduling Flow Redirect Precedence TOS Rate Limiting(Ingress/Egress) Stri Priority
Security Features	Port Security MAC address filter ARP Association (Manual, ARP scanning, DHCP snooping) ARP Protection AAA DAI DoS (Denial of Service) Classification of packages based on: End.MAC, IP End, TCP / UDP Ports, Protocol Type; 802.1x Authentication (port-based e MAC-based) TACACS/TACACS+ Authentication RADIUS Authentication DHCP Filter Guest VLAN SSLv2/SSLv3/TLSv1 SSHv1/SSHv2 Restriction of WEB access based on: IP Address, And. MAC and Port; Port Isolation Loopback detection
Management	SNMP v1/v2c/v3 with Full Private MIBs



	RMON 4 groups WEB (HTTP/HTTPS) CLI (Telnet, Console, SSHv1/v2) Firmware upgrade via console/web/TFTP Configuration Backup/Reload Dual Firmware LLDP Configuration Export/Import CDP Aware OAM (IEEE802.3ah) CFM (IEEE802.1ag) sFlow Telnet client
Other Features	DNS Client DHCP Relay DHCP Client DHCP Snooping DHCP Option 66 DHCP Option 67 DHCP Option 82 NTP/SNTP Client UPNP UDLD
Maintenance	Cable Diagnostics Ping SFP DDM (Digital Diagnostics Monitoring) Thermal protection System log (Local and Remote) Memory and CPU Monitoring Tracert/ tracert 6
Layer 3 functions	
Static Routing	IPv4 Unicast: Static Routing(Software Base) IPv6 Unicast: Static Routing(Software Base)
IPV6	IPv6 neighbor discovery (ND) Path maximum transmission unit (MTU) discovery Internet Control Message Protocol (ICMP) version 6 TCPv6/UDPv6 Ping6 Telnet(v6) Http/Https Interface IPV6 ACL IPV6
Dimension	440x240x44.5 mm
Weight	3,3 kg
Working Temperature	-10 °C to 45 °C



Part No.: 208889
Vendor Part No.: ALL-SG8652M-10G

Storage Temperature	-20 °C to 70 °C
MTBF	50,000hrs

Attributes

Attribute	Value
Anzahl Ports PoE/LAN:	0/48
Belüftung Switch:	Mit Lüfter
Einsatzort Switch:	19"
LAN Geschwindigkeit:	1Gbit/s
Management:	full managed
SFP Geschwindigkeit:	SFP 1Gbit;SFP+ 10Gbit;
SFP Port Anzahl:	4
Weight:	1 Kg
Warranty:	24.00 Months

Accessories

Part No.	Name
101189	ALLNET ALL4757 / Switch module SFP+ (mini Gbic), 10Gbit, SR/
149613	ALLNET Switch Module ALL4757-INDU SFP+(Mini-GBIC), 10Gbit
101190	ALLNET ALL4758 / Switch module SFP+ (mini Gbic), 10Gbit, LR/
149616	ALLNET Switch Module ALL4758-INDU SFP+(Mini-GBIC), 10Gbit
128848	ALLNET Switch Module ALL4760 SFP+(Mini-GBIC), 10Gbit
146282	ALLNET Switch Module ALL4767 SFP+(Mini-GBIC), 10Gbit
27947	ALLNET ALL4750 / Switch module SFP (mini Gbic), 1000Mbit, SX
128033	ALLNET Switch Modul ALL4750-INDU SFP(Mini-GBIC), 1000Mbit MM
59426	ALLNET ALL4751 / Switch module, GBIC mini module, 1000Mbit,
128034	ALLNET Switch Module ALL4751-INDU SFP(Mini-GBIC), 1000Mbit,
114334	ALLNET Switch Modul ALL4752 SFP(mini Gbic), 1000Mbit, LHX/LC
166757	ALLNET Switch Modul ALL4752-INDU SFP(Mini-GBIC), 1000Mbit, LX/LC, 20Km, Singlemode, Industrial, -40/+85 Grad,



Part No.	Name
59391	ALLNET ALL4753 / Switch module GBIC Mini module, 1000Mbit, L
59393	ALLNET ALL4755 / Switch module SFP (mini Gbic), 1000Mbit, ZX
136828	ALLNET Switch Module ALL4761 SFP(Mini-GBIC), 1000Mbit
193149	ALLNET Switch Modul ALL4761-INDU SFP(Mini-GBIC), 1000Mbit, WDM(Bidi)/LC, Tx1310nm/Rx1490nm, 9u, 20Km, Singlemode, Industrial -40/+85 Grad,
136829	ALLNET Switch Module ALL4762 SFP(Mini-GBIC), 1000Mbit
193150	ALLNET Switch Modul ALL4762-INDU SFP(Mini-GBIC), 1000Mbit, WDM(Bidi)/LC, Tx1490nm/Rx1310nm, 9u, 20Km, Singlemode, Industrial -40/+85 Grad,
140675	ALLNET Switch Module ALL4765 SFP(Mini-GBIC), 1000Mbit
143548	ALLNET Switch Module ALL4756 SFP(Mini-GBIC), 1000Mbit, ZX/LC
208404	ALLNET Switch Modul ALL4765-INDU SFP(Mini-GBIC), 1000Mbit, RJ45(TP), Industrial -40/+85 Grad,
75932	Patchkabel RJ45, CAT5e 100Mhz, 0,25m grau, FTP(F/UTP), Synergy 21,
75939	Patchkabel RJ45, CAT5e 100Mhz, 0,5m grau, FTP(F/UTP), Synergy 21,
75959	Patchkabel RJ45, CAT5e 100Mhz, 2m grau, FTP(F/UTP), Synergy 21,
75966	Patchkabel RJ45, CAT5e 100Mhz, 3m grau, FTP(F/UTP), Synergy 21,
75973	Patchkabel RJ45, CAT5e 100Mhz, 5m grau, FTP(F/UTP), Synergy 21,
76091	Patchkabel RJ45, CAT5e 100Mhz, 15m grau, S-FTP(SF/UTP), Synergy 21,
76029	Patchkabel RJ45, CAT5e 100Mhz, 0,25m grau, S-FTP(SF/UTP), Synergy 21,
76036	Patchkabel RJ45, CAT5e 100Mhz, 0,5m grau, S-FTP(SF/UTP), Synergy 21,
76056	Patchkabel RJ45, CAT5e 100Mhz, 2m grau, S-FTP(SF/UTP), Synergy 21,
76077	Patchkabel RJ45, CAT5e 100Mhz, 7,5m grau, S-FTP(SF/UTP), Synergy 21,
76091	Patchkabel RJ45, CAT5e 100Mhz, 15m grau, S-FTP(SF/UTP), Synergy 21,
76117	Patchkabel RJ45, CAT6 250Mhz, 0,25m grau, S-STP(S/FTP), LSZH, Synergy 21,
76124	Patchkabel RJ45, CAT6 250Mhz, 0,5m grau, S-STP(S/FTP), LSZH, Synergy 21,
76133	Patchkabel RJ45, CAT6 250Mhz, 1,0m grau, S-STP(S/FTP), LSZH, Synergy 21,
76151	Patchkabel RJ45, CAT6 250Mhz, 2m grau, S-STP(S/FTP), LSZH, Synergy 21,
76160	Patchkabel RJ45, CAT6 250Mhz, 3m grau, S-STP(S/FTP), LSZH, Synergy 21,
76169	Patchkabel RJ45, CAT6 250Mhz, 5m grau, S-STP(S/FTP), LSZH, Synergy 21,
76178	Patchkabel RJ45, CAT6 250Mhz, 7,5m grau, S-STP(S/FTP), LSZH, Synergy 21,
76187	Patchkabel RJ45, CAT6 250Mhz, 10m grau, S-STP(S/FTP), LSZH, Synergy 21,
76196	Patchkabel RJ45, CAT6 250Mhz, 15m grau, S-STP(S/FTP), LSZH, Synergy 21,
140955	TP(RJ45) POE-Tester, at/af, Endspan/Midspan, standard, Synergy 21,



Part No.: 208889
Vendor Part No.: ALL-SG8652M-10G

Part No.	Name
141255	Netzkabel 230V Schutzkontakt CEE7(Stecker)->Kaltgeräte IEC-C13(Buchse), 1m,Black IEC Lock
141254	Netzkabel 230V Schutzkontakt CEE7(Stecker)->Kaltgeräte IEC-C13(Buchse), 2m,Black IEC Lock
141256	Netzkabel 230V Schutzkontakt CEE7(Stecker)->Kaltgeräte IEC-C13(Buchse), 3m,Black IEC Lock
191685	ALLNET Switch Modul ALL4768 SFP+(Mini-GBIC), 10Gbit, ER/LC, bis 40Km, Singlemode,
191686	ALLNET Switch Modul ALL4769 SFP+(Mini-GBIC), 10Gbit, ZR/LC, bis 80Km, Singlemode,
188424	CyberPower USV, OR-Serie, 600VA/360W, Line-Interactive, LCD, 19"/1HE, USB/RS232, IEC C13 Kaltgeräte,
188433	CyberPower USV, OR-Serie, 650VA/360W, Line-Interactive, LCD, 19"/1HE, USB/RS232, CEE7-Schutzkontakt,
175260	GBIC-Mini, SFP+, 10GB, TP(RJ45), 10GBASE-T, kompatibel für Intel, Intel-Code
98686	ALLNET MSR control center "ALL3500v2" incl. 4 sensor ports & WLAN for IP building automation
104126	ALLNET ALL3505 / IP Homeautomation Appliance DIN-Rail 8x I2C
134571	ALLNET ALL3419 / IP Building-Autom. 3x I2C, 1x USB, LAN/WLAN
206211	ALLNET MSR Central "ALL5000v2" incl. 16 Sensor Ports & 19" for IP Building Automation
192187	ALLNET PoE RGBW lamp with 1x MSR sensor port / LAN / WIFI *ALL-PoE-RGBW-LAMP*
234699	ALLNET Switch full managed Layer2+ zbh. Replacement bracket for ALL-SGxx 18/26/28/54 - Short version