ALLNET Meetingraum RGB LED Tablet 10 Zoll RK3576 Android 16 und NFC/RFID Farbe schwarz

>>> Zum Shop-Artikel



EAN CODE

4 0 3 8 8 1 6 2 5 6 8 8 1

ALLNET MeetTwo Serie mit RK3576. Die bisher schnellste Plattform für unser neues Sortiment.

Inklusive Netzteil und integrierter snap-in Wandhalterung mit Diebstahlschutz. RGB LED zur Anzeige z.B. von Warnsignalen, Belegung von Meetingräumen etc.

Durch das NFC lassen sich auch sehr gut Zeiterfassungsterminals umsetzen oder Info Terminals mit ID, wie z.B. Mehrparteien Wohnanlagen.

Die API/SDK für NFC/RFID und LED, finden Sie auf https://firmware.allnet.de

Download Android 16

NFC Detail:

Item	Type	Tested
1	ISO/IEC 18092(NFCIP-1)	yes
2	ISO/IEC 21481(NFCIP-2)	yes
3	ISO/IEC 14443A	yes
4	ISO/IEC 14443B	yes
5	ISO/IEC 15693	yes
6	Mifare Classic	yes
7	Mifare Ultralight	yes
8	MIFARE DESFire EV1/ EV2/EV3	yes

9	Sony FeliCa		yes		
System	CPU				RK3576S Quad core cortex A53+Quad core cortex A72
	RAM				4GB
	Internal memory				32GB
	Operation system				Android 16
	Touch screen				10-Point capacitive touch
Display	Panel				10.1"LCD panel
	Panel Type				IPS
	Resolution				1280*800
	Display Colors				16.7M Colors
	Viewing angle				R/L 85/85, U/D 85/85
	Display mode				Normally black
	Contrast ratio				1500:1
	Response Time				25ms
	Back-light Type				ELed
	Luminance				280cd/m2
	Aspect Ratio				,16:10
Network	WiFi				IEEE 802.11a/b/g/n/ac/ax
	Buletooth				Bluetooth 5.4
	Ethernet				10M/100M/1000M ethernet
Interface	SIM Slot				4G Flow Card
	SD Slot				SD card ,Max support to 64GB
	Earphone				3.5mm earphone + Microphone
	USB				USB 3.0 host

	USB				USB for serial (TTL Level) ,Optional USB Host
	RJ45				Ethernet interface
	Type-C				Only supports ADB function
	Power jack				DC power input
Media play	Video format				MPEG-1,MPEG-2,MPEG-4, H.265,H.264,VP9,AV1, AVS2 ,MVC,AVC ,etc., support up to 4K
	Audio format				MP3/WMA/AAC/WAV/OGG, etc
	Photo				JPEG/PNG/GIF,etc
Other	Product Colors				White/Black
	VESA				75*75 mm
	Button				Power
	G-sensor				Support 90 degrees
	Speaker				2*2W
	Microphone				Single microphone
	NFC				Optional,13.56 MHz,ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic

					encrypted tags and cards
	RFID				Optional ,125k,ISO/IEC 11784/11785, EM4100,TK4100/GK4100
	LED light bar				LED light bar with RGB and mixed color
	Camera				Routine angle 5.0MP with mipi
	4G Moduel				Optional
	Language				Multi-language
	Certificates				CCC/CE/FCC
	POE				Support IEEE802.3at,up to 30W
Working Surrounding	Working Temperature				0°C---40°C
	Storage Temperature				-20°C---60°C
	Working Humidity				20~80%RH
	Storage Humidity				10~95%RH
Accessories	Adapter				Adapter,12V/1.5A
	User manual				*1

Merkmale

Merkmal	Wert
Abmessung:	259.36 x 278.36 x 28
Alternative Betriebssysteme:	Linux;
Arbeitsspeicher (RAM):	4
Auflösung Panel:	1280x800
Betriebssystem:	Android 16
Bluetooth:	ja
Chipset:	RK3576

Merkmal	Wert
Diagonale:	10
Einsatzbereiche:	Indoor
Farbe Displayrand:	schwarz
Farbe Gehäuse:	schwarz;
Hauptspeicher:	32
IP Schutzklasse Display:	IP 20
Kamera:	ja
Mobilfunk:	nein
Montageart:	integrierte Halterung;
NFC&RFID:	13,56MHz
Produktart:	Tablet
Stromversorgung:	PoE&Netzteil
Touchscreen:	kapazitiv
WLAN:	2,4&5
Gewicht:	1,418 Kg
Garantie:	24.00 Monate

ALLNET GmbH - Maistraße 2 - 82110 Germering - sales@allnet.de - 089 / 894 222 22

Irrtümer und Änderungen vorbehalten.