

WavePOS 68



 Ready in Windows System



True Flat Screen

















VFD Easy Installation



Hard Disk Quick Maintenance



2nd LCD Display

Model	WavePOS 68		Features
CPU	Intel® Haswell / Skylake Core™ i3 / i5 / i7	Intel® Celeron® Bay Trail J1900 Processor	
Display	15" TFT LCD Panel		
Resolution	1024 x 768		
Brightness	300 nits		
Touch Screen	PCAP Multitouch Screen	5 Wires Resistive PCAP Multitouch Screen	
Memory	4G / 8GB DDR3L	4G / 8GB DDR3 / DDR3L	
Storage	2.5" SATA HDD SSD SATA Interface Max. 1 TB		
Network	10/100/1000 Base-T Gigabit Ethernet		Option Peripherals
Power	12V DC-IN		
Weight	6.0 kgs	5.8 kgs	
Dimension	384 x 330 x 194 mm (WxHxD)	384 x 324 x 194 mm (WxHxD)	
OS	POSReady 7, Windows 7 / 8 / 10 IoT		
Environmental	0°C ~ 40°C, 20% RH ~ 80% RH (Operating) -20°C ~ 60°C, 10% RH ~ 90% RH (Storage)		
Safety	CCC / CE / FCC		
Audio	2 x Speaker	—	
Internal	1 x mPCIe	—	
Connectivity	2 x 2.0 USB, 2 x 3.0 USB, 1x VGA, 4 x COM, 1 x RJ45 1 x RJ11, 1 x LPT, 1 x DC-IN	3 x 2.0 USB, 1 x 3.0 USB, 1x VGA, 3 x COM, 1 x RJ45, 1 x RJ11, 1 x DC-IN	
I/O Ports	