


>>> Vers l'article de la boutique en ligne



EAN CODE



Le lecteur multimédia Android puissant S905X4 Pro

Amlogic S905X4 4GB DDR4/32GB de stockage, HDMI 2.1, WIFI 6 2,4/5,8GHz @80MHz Bandbreite, 4K, USB 3.0

Notre nouveau lecteur multimédia est un petit lecteur très puissant avec **Android 11**. Le lecteur peut être utilisé comme une télévision boîte ainsi que comme un lecteur multimédia numérique. La connexion au magasin d'applications de Google vous donne accès à des millions d'applications.

Le lecteur peut être utilisé avec des écrans appropriés jusqu'à une résolution **4K** sur des appareils et des câbles certifiés **HDMI 2.0**. Une rotation native de l'écran est possible, ce qui permet de lire le contenu également dans le format portrait. Avec les **4GB DDR4 RAM**, le lecteur a une **bonne performance** dans la lecture vidéo et le stockage ne se remplit pas aussi rapidement que les variantes 2GB. Les **32GB de stockage flash** offrent suffisamment d'espace pour stocker du contenu numérique hors ligne. Une sortie audio numérique **SPDIF**

The **32GB storage** offers enough space to store Digital Signage content offline. A digital SPDIF audio output provides the optimal cinema experience via a cinema sound system. The control can be done via an optional keyboard and mouse or via the remote control included in the delivery.

With WIFI 6 and WPA3 encryption, this player is up to date and equipped with sufficient speed and security.

Download Firmware and OTA Update: <https://fileshare.allnet.de/s/ssIV1H0N36JV08D>

Highlights:



No. d'article: 224334
Numéro de fabricant: ALL-S905X4W6

- ALLNET Digital Signage Android Player S905X4 Pro
- Amlogic S905X4 Quad Core ARM Cortex-A55 CPU ARM G31 MP2 GPU
- HDMI compatible to 2.1 to support maximum 4K@60fps output (HDCP2.2)
- DDR4 4GB/ EMMC 32GB
- Android 11
- **1*RJ45 1000M (Gigabit network)**
- WLAN 2,4/5,8GHz a/b/g/n/ac/ax
- Bluetooth 4.0 (2,4GHz)
- USB-C 2.0 OTG + 1*USB 3.0 host
- SPDIF
- Touchscreen HID driver integrated, enables the use of touchscreens

ALLNET Mediaplayer S905X4		
CPU	Amlogic S905X4 64-bit quad core ARM® Cortex™ A55 CPU	
GPU	G31™ MP2 GPU processor	
Memory	DDR3: 4GB	
Flash	eMMC: 32GB (Option: 64GB/128GB MOQ 500Stück)	
WiFi	IEEE 802.11 a/b/g/n/ac ; 2.4G / 5G	
Bluetooth	BT ; Support Voice Remote	
Moudle	Plastic : Black Color	
I/O	1*HDMI	HDMI 2.1 ,Support HDMI CEC, Dynamic HDR and and 8Kx4K@24 max resolution output
	1*AV OUT	480i/576i standard definition output
	2*USB	1 * USB 3.0 ; 1*USB 2.0
	1*IR Reciver	Remote Receiver Connect
	1*RJ45	Ethernet Interface;Support 10/100/ 1000M
	1*TF CARD	Support 4GB/8GB/16GB/32GB/64GB
Power	DC 5V/2A;DC PLUG 5,5mm	
Software		
OS	Android 11.0	
Video	• Amlogic Video Engine (AVE) with dedicated hardware decoders and encoders • Support multi-video decoder up to 4x1080P@60fps • Supports multiple “secured” video decoding sessions and simultaneous decoding and encoding • Video/Picture Decoding/AV1 MP-10@L5.1 4Kx2K@60fps • VP9 Profile-2 up to 8Kx4K@24 fps • H.265 HEVC MP-10@L5.1 up to 8Kx4K@24 fps • VS2-P2 Profile up to 8Kx4K@24 fps • H.264 AVC HP@L5.1 up to 4Kx2K@30fps • MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) • WMV/VC-1 SP/MP/AP up to 1080P@60fps • AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps	



No. d'article: 224334
 Numéro de fabricant: ALL-S905X4W6

	• MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) • MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) • RealVideo 8/9/10 up to 1080P@60fps • Multiple language and multiple format sub-title video support • MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918) • Supports JPEG thumbnail, scaling, rotation and transition effects • Supports *.mkv,*.wmv,*.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats	
Audio	Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing Low-power VAD Built-in serial digital audio SPDIF/IEC958 input/output and PCM input/output 3 built-in TDM/PCM/I2S ports with TDM/PCM mode up to 384kHz x 32bits x 16ch or 96kHz x 32bits x 32ch and I2S mode up to 384kHz x 32bits x 16ch Digital microphone PDM input with programmable CIC, LPF & HPF, support up to 8 DMICs Built-in stereo audio DAC Supports concurrent dual audio stereo channel output with combination of analog+PCM or I2S+PCM	
Image	HD JPEG. BMP. GIF. PNG. TIF	
Language	English French German Spanish Italian etc multilateral languages	
Applications		
Apps	Apps download freely form android market. amazon app store etc.	
Medium	Local Media playback,Support HDD, U Disk ,TF Card	
Packing	Product dimension	105*20
	Qty per unit packing	1pc
	Unit packing: (LxWxH)	(MM)
	Unit packing (G.W.)	0.4KG
	Qty per export carton	20PCS
	Export carton (WxHxL)	(MM)
	Export carton (G.W.)	8KG
Accessories :		
1. HDMI cable *1		
2. IR Remote *1 (RC-05*		
3. User Manual *1		
4. Package box *1		
5. Power adapter *1		

Accessoires



No. d'article: 224334
Numéro de fabricant: ALL-S905X4W6

No. d'article	Désignation
214123	ALLNET Air Mouse G10 Pro Remote Control 2.4GHz USB Dongle with Infrared