



MATERIAL LIST:

| | | | | |
|---|---------------|--|---|--|
| ⑦ | Dust cap | Polycarbonate Transparent black | 1 | |
| ⑥ | Boot | Polycarbonate Transparent black | 1 | |
| ⑤ | Housing | zinc alloy | 1 | |
| ④ | MODULAR COVER | PC with label color code T568B/T568A | 1 | |
| ③ | RJ 45 Plug | 8P8C 3U" GOLD PLATED | 1 | |
| ② | PCB | 1.0mm UL 94V0 | 1 | |
| ① | IDC | FOR 22-26AWG (0.40mm-0.65mm) CABLE, PHOSPHOR BRONZE & TINNED | 1 | |

NOTE:

100% OPEN SHORT & MISS WIRE TEST;
 CAT. 6A/Class EA Channel Test pass
 ISO/IEC 11801-1:2017 (Ed. 1.0)/IEC60603-7 and PoE per IEEE 802.3af, PoE+ per IEEE 802.3at
 Compact cable manager for round Solid cable AWG22/1-26/1(1/0.65-1/0.4mm) and stranded cable AWG 22/7-26/7
 For cable OD:6.0-8.5mm
 RoHS 3.0 and REACH Compliant
 Storage Temperature : -40°C-+70°C
 Operation Temperature : -10°C-+60°C
 PACKING:1PC/PE BAG+user manual

| NO. | PARTS NAME | SPECIFICATION STANDARD | QT' Y | REMARK |
|-----|------------|-----------------------------------|------------|--------|
| | | | | |
| | | | | |
| BY | CHK | NEW REVISION RECORD MODIFICATIONS | 2024-06-05 | A |

| SYNERGY 21 | | | | | |
|--------------|---|---------------------|------------|------|----|
| CUSTOMER | | ITEM NO. | S216345 | | |
| PRODUCT NAME | Field Installable RJ 45 shielded connector Cat6A/Class EA | manufacture country | CHINA | UNIT | MM |
| DRAWNBY | CHECKBY | APPOBY | DATE | | |
| SYNERGY 21 | SYNERGY 21 | SYNERGY 21 | 2024-06-05 | | |