ALLNET Meetingraum RGB LED Tablet 13 Zoll RK3576 Android 16 und NFC/RFID Farbe weiß

>>> Zum Shop-Artikel



EAN CODE

4 0 3 8 8 1 6 2 5 7 0 8 6

ALLNET Meetingraum RGB LED Tablet 13 Zoll RK3576 Android 16 und NFC/RFID Farbe weiß

Inklusive Netzteil und integrierter snap-in Wandhalterung mit Diebstahlschutz. RGB LED zur Anzeige z.B. von Warnsignalen, Belegung von Meetingräumen etc.

Durch das NFC lassen sich auch sehr gut Zeiterfassungsterminals umsetzen oder Info Terminals mit ID, wie z.B. Mehrparteien Wohnanlagen.

Die API/SDK für NFC/RFID und LED, finden Sie auf https://firmware.allnet.de

Download Android 16

System	CPU	RK3576S Quad core cortex A53+Quad core cortex A72
	RAM	4GB
	Internal memory	32GB
	Operation system	Android 16
	Touch screen	10-point capacitive touch
Display	Panel	15 Zoll LCD panel
	Panel Type	IPS
	Resolution	1280*800
	Display	16.7M Colours

	Colours	
	Viewing angle	R/L 85/85, U/D 85/85
	Display mode	Normally black
	Contrast ratio	1500:1
	Response Time	25ms
	Back-light Type	ELed
	Luminance	280cd/m2
	Aspect Ratio	16:9
Network	WiFi	IEEE 802.11a/b/g/n/ac/ax
	Buletooth	Bluetooth 5.4
	Ethernet	10M/100M/1000M ethernet
Interface	SIM slot	not inlcluded
	SD slot	SD card ,Max support to 64GB
	Earphone	3.5mm earphone + Microphone
	USB	USB 3.0 host
	USB	USB for serial (TTL Level) ,Optional USB Host
	RJ45	Ethernet interface
	Type-C	Only supports ADB function
	Power jack	DC power input
Media play	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VP9,AV1, AVS2,MVC,AVC ,etc., support up to 4K
	Audio format	MP3/WMA/AAC/WAV/OGG, etc
	Photo	JPEG/PNG/GIF,etc
Other	Product Colours	White/Black
	VESA	75*75 mm
	Button	Power
	G-sensor	Support 90 degrees
	Speaker	2*2W
	Microphone	Single microphone
	NFC	Optional,13.56MHz,ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic encrypted tags and cards
	RFID	Optional ,125k,ISO/IEC

		11784/11785, EM4100,TK4100/GK4100
	LED light bar	LED light bar with RGB and mixed colour
	Camera	Routine angle 5.0MP with mipi
	4G Moduel	Optional
	Language	Multi-language
	Certificates	CCC/CE/FCC
	POE	Support IEEE802.3at,up to 30W
Working Surrounding	Working Temperature	0°C---40°C
	Storage Temperature	-20°C---60°C
	Working Humidity	20~80%RH
	Storage Humidity	10~95%RH
Accessories	Adapter	Adapter,12V/1.5A
	User manual	*1

Merkmale

Merkmal	Wert
Abmessung:	333,0 x 225,0 x 28,5
Alternative Betriebssysteme:	Linux;
Arbeitsspeicher (RAM):	8
Auflösung Panel:	1920x1080
Betriebssystem:	Android 16
Bluetooth:	ja
Chipset:	RK3576
Diagonale:	13
Einsatzbereiche:	Indoor

Merkmal	Wert
Farbe Displayrand:	weiß
Farbe Gehäuse:	weiß
Hauptspeicher:	32
IP Schutzklasse Display:	IP 20
Kamera:	ja
Mobilfunk:	nein
Montageart:	integrierte Halterung;
NFC&RFID:	13,56MHz
PoE Klasse:	802.3at 12,95-25,50 W Class 4
Produktart:	Tablet
Stromversorgung:	PoE&Netzteil
Touchscreen:	kapazitiv
WLAN:	2,4&5
Gewicht:	2,75 Kg
Garantie:	24.00 Monate