


Synergy 21 LED light panel 300*1200 Up& Down PONTOS-T NW / W



kwh/1000h:	44,00
Lumens:	4000
Watt:	40,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



Ultra Slim LED Panel Light Model PONTOS transparent
Suitable for ceiling suspension



Frame colour: white
Power consumption: 40Watt
Number of lumens: 3400lm (total) 50%UP 50%DOWN
Light colour: 4000k
MacAdam/SDCM = 3
Colour rendering: >CRI 80
Beam angle: 240° (total)
120°(downwards)
120° (upwards)
Protection class: IP20 and IK08
Operating temperature: -20°C to +60°C (Amb.)
Power supply: 1050mA, see accessories for power supply unit
Size: 295mm x 1195mm x 15mm
Mounting kit incl.

Energy efficiency class: A
kWh/1000h: 44


Attributes

Attribute	Value
Abstrahlwinkel:	240
Ampere:	1.05
CRI:	80
Dimmbar:	Nein
Grösse:	300*1200
LED - Gehäusefarbe:	weiß
Lichtfarbe:	neutralweiß
Lichtfarbe in Kelvin:	4000
Lumen:	3400
Weight:	2.3 Kg
Warranty:	60.00 Months

Additional Images



40W, 300*1200mm



Accessories

Part No.	Name
131690	Synergy 21 LED light panel 300*1200 Up& Down or Pontos transparent cable for power supply unit
127397	Mean Well power supply - CC Driver 1050mA 34~57V Triac dimm
134899	Synergy 21 Netzteil - Einschaltstrombegrenzer OSRAM
167277	Mean Well power supply - CC Driver 1050mA ~190V 0-10V dimm
167278	Mean Well power supply - CC Driver 1050mA ~238V 0-10V dimm
167276	Mean Well power supply - CC Driver 1050mA ~215V 0-10V dimm