

DATASHEET

IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug,
1.0m



General data

IP67 cable gland with pre-installed Cat.6A TM31 RJ45 S/FTP cable plug / plug
For installation in housings with M25 cut-out
Gland material: brass

Technical properties

AWG-size	26/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	put-on
Cable construction	4x2
Cable type	S/FTP
Cable type acc. to Manufacturer	Draka UC900 SS26
Category	6A (TIA)
Colour anti-kink sleeve	blue
Colour outer sheath	blue
Conductive shield	360° shield contact
Connector type	TM31

DATASHEET

IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug, 1.0m

Contacts	Gold plated
Jacket material	LSZH
Locking lever	True
Model	shielded
Oil resistant	no
Ozone resistance	No
Pin assignment	1:1
Raw cable	Cat.7
Resistant to chemicals	False
Suitable for degree of protection (IP)	IP67
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Type of housing	Brass nickel-plated
Type of locking	M25
UL approved	False
UV resistant	no

Available variants

ArtNr.	Bezeichnung	Length
IP67KVRJ45TM31-1,0	IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug, 1.0m	1.0 m
IP67KVRJ45TM31-5,0	IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug, 5.0m	5.0 m
IP67KVRJ45TM31-10,0	IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug, 10.0m	10.0 m


Drawings

DATASHEET

IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug,
1.0m

Frontplattenausschnitt

Frontplatte bis 8mm



DATASHEET

IP67 Cable gland, M25, RJ45 TM31, Plug to TM31 Plug, 1.0m

