

# 2/4/8-Port USB DVI/HDMI/DisplayPort Single/Dual Display Secure KVM Switch Series

## PSS PP v3.0 Secure KVM Switch Series

- ATEN PSS PP v3.0 Secure KVM Switches are specifically designed to meet the stringent security requirement of secure defense and intelligence installations. ATEN PSS PP v3.0 Secure KVM Switches are compliant with PSS PP v3.0 (Protection Profile for Peripheral Sharing Switch, Version 3.0) standard certified by the National Information Assurance Partnership (NIAP).

ATEN PSS PP v3.0 Secure KVM Switches provide isolation between computer sources and peripherals while sharing a single keyboard, mouse, monitor, speaker set, and Common Access Card (CAC) reader between connected computers of various security classifications. Compliance with PSS PP v3.0 ensures peripheral sharing capabilities provide maximum user data security when switching port focus, preventing unauthorized data flows or leakage between connected sources. Key protections include isolation and unidirectional data flow, restricted peripheral connectivity and filtering, user data protection, configurable device filtering and management, and always-on tamper-proof design, keeping sensitive assets isolated and providing advanced security and a user friendly design for instantly secure deployment.

To fulfill different customer demands, ATEN PSS PP v3.0 Secure KVM Switches offer a wide range of options including 2-port, 4-port and 8-port models, and video interfaces including DisplayPort\*, HDMI, and DVI. ATEN PSS PP v3.0 Secure KVM Switches also provide customers with the flexibility to connect single or dual displays, providing up to 4K UHD (3840 × 2160 @30Hz) video quality.

With multi-layered security, ATEN PSS PP v3.0 Secure KVM Switches ensure high-level desktop security and data safekeeping for applications such as government agencies, finance, and other organizations that often handle sensitive or confidential data on separate networks.

Note: \*Console video output of DisplayPort models is converted to HDMI



CS1182DP Front view



CS1182DP Rear view



CS1184H Front view



CS1184H Rear view



CS1148D Front view



CS1148D Rear view



## Features


- Superior video quality – up to 4K (3840 x 2160 @ 30 Hz)\*
- Port selection via pushbuttons only to enhance security
- Video DynaSync™ – Exclusive ATEN technology eliminates boot-up display problems and optimizes resolutions when switching between ports
- Supports enable/disable CAC function by port
- LED indicators for peripheral filtering and KVM security status
- Rugged metal enclosure
- Built-in internal power
- Supports analog audio (speaker only)\*\*

\* HDMI and DisplayPort Secure KVM Switch series supports console video output resolutions up to 4K @ 30 Hz. DVI Secure KVM Switches offer 3840 x 2160 @ 30 Hz video output on compatible HDMI-interfaced monitors/computers with ATEN DVI-to-HDMI KVM cables.

\*\* Only analog speaker data input is supported. The ATEN PSS PP v3.0 Secure KVM Switches does not convert digital audio to analog audio.

## Highlights

<b>NIAP Common Criteria Compliant</b>	<ul style="list-style-type: none"> <li>Compliant with PSS PP v3.0 (Protection Profile for Peripheral Sharing Switch, Version 3.0) security requirements</li> </ul>
<b>Multi-Layered Security</b>	<ul style="list-style-type: none"> <li>Restricted USB Connectivity – non-authorized HID's (Human Interface Devices) or non-predefined CAC devices will be rejected / ignored</li> <li>Always-on Chassis Intrusion Detection – renders the ATEN PSS PP v3.0 Secure KVM Switches inoperable when physical tampering is detected</li> <li>Tamper-Evident Seals– provides visual indication of any attempt to access the ATEN PSS PP v3.0 Secure KVM Switches' internal components</li> <li>Non-Reprogrammable Firmware – prevents reprogramming the ATEN PSS PP v3.0 Secure KVM Switches</li> </ul>
<b>Data Channel Isolation and Unidirectional Data Flow</b>	<ul style="list-style-type: none"> <li>Data Channel Isolation – prevents data leakage between connected computers via isolated channel per port</li> <li>Unidirectional Data Flow – ensures unidirectional data flow between the console devices and the selected computer</li> <li>ATEN PSS PP v3.0 Secure KVM Switches control and isolate data flow between the console devices and connected computers</li> </ul>
<b>User Data Protection</b>	<ul style="list-style-type: none"> <li>User Data Protection – Keyboard/Mouse data buffer is automatically purged when switching KVM port focus</li> </ul>
<b>Security Management</b>	<ul style="list-style-type: none"> <li>KVM Log Data – provides administrative functions for authorized administrator to audit KVM log data</li> <li>Configurable Device Filtering – USB CAC Port can be configured to allow/reject whitelisted / blacklisted devices via Admin logon function or Windows-based application</li> </ul>



# Specifications

## ATEN PSS PP v3.0 DisplayPort Secure KVM Switches

Function	CS1182DP	CS1184DP	CS1188DP
Computer Connections	2	4	8
Port Selection	Pushbutton		
<b>Connectors</b>			
Console Ports	2 x USB Type-A Female (Black) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDMI Female (White) 1 x Mini Stereo Jack Female (Green; front panel)		2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDMI Female (White) 1 x Mini Stereo Jack Female (Green; front panel)
KVM Ports	4 x USB Type-B Female (White)	8 x USB Type-B Female (White)	16 x USB Type-B Female (White)
	2 x DisplayPort Female (Black)	4 x DisplayPort Female (Black)	8 x DisplayPort Female (Black)
	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)	8 x Mini Stereo Jack Female (Green)
Power	1 x 3-prong AC Socket		
USB CAC Port	1 x USB Type-A Female (White; front panel)		
<b>Switches</b>			
Port Selection	2 x Pushbuttons	4 x Pushbuttons	8 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker		
<b>LEDs</b>			
On Line / Selected (KVM Port)	2 (Orange)	4 (Orange)	8 (Orange)
Online / Selected (CAC Port)	2 (Green)	4 (Green)	8 (Green)
Video	1 (Green)		
Key Lock	3 (Green)		
Power	1 (Blue)		
<b>Emulation</b>			
Keyboard / Mouse	USB		
<b>Video</b>			
Maximum Input Power Rating	Max. 3840 x 2160 @ 30 Hz (UHD)		
Power Consumption	AC110V:3.8W AC220V:3.8W	AC110V:5W AC220V:4.7W	AC110V:10W AC220V:9.4W
<b>Environmental</b>			
Operating Temperature	0-50°C		
Storage Temperature	-20-60°C		
Humidity	0 - 80% RH, Non-condensing		
<b>Physical Properties</b>			
Housing	Metal		
Weight	1.78 kg	1.79 kg	3.05 kg
Dimensions (L x W x H)	33.50 x 16.40 x 4.40 cm	33.50 x 16.40 x 4.40 cm	43.20 x 20.50 x 6.60 cm

**ATEN PSS PP v3.0 DisplayPort Dual Display Secure KVM Switches**

Function	CS1142DP	CS1144DP	CS1148DP
<b>Computer Connections</b>	2	4	8
<b>Port Selection</b>	Pushbutton		
<b>Connectors</b>			
Console Ports	2 x USB Type-A Female (Black) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 2 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel)		2x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 2 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel)
KVM Ports	4 x USB Type-B Female (White)	8 x USB Type-B Female (White)	16 x USB Type-B Female (White)
	4 x DisplayPort Female (Black)	8 x DisplayPort Female (Black)	16 x DisplayPort Female (Black)
	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)	8 x Mini Stereo Jack Female (Green)
Power	1 x 3-prong AC Socket		
USB CAC Port	1 x USB Type-A Female (White; front panel)		
<b>Switches</b>			
Port Selection	2 x Pushbuttons	4 x Pushbuttons	8 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker		
<b>LEDs</b>			
On Line / Selected (KVM Port)	2 (Orange)	4 (Orange)	8 (Orange)
Online / Selected (CAC Port)	2 (Green)	4 (Green)	8 (Green)
Video	2 (Green)		
Key Lock	3 (Green)		
Power	1 (Blue)		
<b>Emulation</b>			
Keyboard / Mouse	USB		
<b>Video</b>			
Maximum Input Power Rating	Max. 3840 x 2160 @ 30 Hz (UHD) 100-240V~; 50-60 Hz; 1A		
Power Consumption	AC110V:5.5W AC220V:5.3W	AC110V:8.2W AC220V:8W	AC110V:16W AC220V:16W
<b>Environmental</b>			
Operating Temperature	0-50°C		
Storage Temperature	-20-60°C		
Humidity	0 - 80% RH, Non-condensing		
<b>Physical Properties</b>			
Housing	Metal		
Weight	2.12 kg	2.13 kg	3.35 kg
Dimensions (L x W x H)	33.50 x 16.40 x 6.60 cm	33.50 x 16.40 x 6.60 cm	43.20 x 20.50 x 6.60 cm

**ATEN PSS PP v3.0 HDMI Secure KVM Switches**

Function	CS1182H	CS1184H	CS1188H
<b>Computer Connections</b>	2	4	8
<b>Port Selection</b>	Pushbutton		
<b>Connectors</b>			
Console Ports	2 x USB Type-A Female (Black) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel)		2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel)
KVM Ports	4 x USB Type-B Female (White)	8 x USB Type-B Female (White)	16 x USB Type-B Female (White)
	2 x HDMI Female (Black)	4 x HDMI Female (Black)	8 x HDMI Female (Black)
	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)	8 x Mini Stereo Jack Female (Green)
Power	1 x 3-prong AC Socket		
USB CAC Port	1 x USB Type-A Female (White; front panel)		
<b>Switches</b>			
Port Selection	2 x Pushbuttons	4 x Pushbuttons	8 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker		
<b>LEDs</b>			
On Line / Selected (KVM Port)	2 (Orange)	4 (Orange)	8 (Orange)
Online / Selected (CAC Port)	2 (Green)	4 (Green)	8 (Green)
Video	1 (Green)		
Key Lock	3 (Green)		
Power	1 (Blue)		
<b>Emulation</b>			
Keyboard / Mouse	USB		
<b>Video</b>	Max. 3840 x 2160 @ 30 Hz (UHD) ; 1920 x 1080 (FHD)		
Maximum Input Power Rating	100-240V~; 50-60 Hz; 1A		
Power Consumption	AC110V:2.8W AC220V:2.4W	AC110V:3W AC220V:3.1W	AC110V:6W AC220V:6.2W
<b>Environmental</b>			
Operating Temperature	0-50°C		
Storage Temperature	-20-60°C		
Humidity	0 - 80% RH, Non-condensing		
<b>Physical Properties</b>			
Housing	Metal		
Weight	1.78 kg	1.79 kg	3.05 kg
Dimensions (L x W x H)	33.50 x 16.40 x 4.40 cm	33.50 x 16.40 x 4.40 cm	43.20 x 20.50 x 6.60 cm

**ATEN PSS PP v3.0 HDMI Dual Display Secure KVM Switches**

Function	CS1142H	CS1144H	CS1148H
<b>Computer Connections</b>	2	4	8
<b>Port Selection</b>	Pushbutton		
<b>Connectors</b>			
Console Ports	2 x USB Type-A Female (Black) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 2 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel)		2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 2 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel)
KVM Ports	4 x USB Type-B Female (White)	8 x USB Type-B Female (White)	16 x USB Type-B Female (White)
	4 x HDMI Female (Black)	8 x HDMI Female (Black)	16 x HDMI Female (Black)
	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)	8 x Mini Stereo Jack Female (Green)
Power	1 x 3-prong AC Socket		
USB CAC Port	1 x USB Type-A Female (White; front panel)		
<b>Switches</b>			
Port Selection	2 x Pushbuttons	4 x Pushbuttons	8 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker		
<b>LEDs</b>			
On Line / Selected (KVM Port)	2 (Orange)	4 (Orange)	8 (Orange)
Online / Selected (CAC Port)	2 (Green)	4 (Green)	8 (Green)
Video	2 (Green)		
Key Lock	3 (Green)		
Power	1 (Blue)		
<b>Emulation</b>			
Keyboard / Mouse	USB		
Video	Max. 3840 x 2160 @ 30 Hz (UHD) ; 1920 x 1080 (FHD)		
Maximum Input Power Rating	100-240V~; 50-60 Hz; 1A		
Power Consumption	AC110V:4.5W AC220V:4.2W	AC110V:3.9W AC220V:3.6W	AC110V:8W AC220V:7.2W
<b>Environmental</b>			
Operating Temperature	0-50°C		
Storage Temperature	-20-60°C		
Humidity	0 - 80% RH, Non-condensing		
<b>Physical Properties</b>			
Housing	Metal		
Weight	2.12 kg	2.13 kg	3.35 kg
Dimensions (L x W x H)	33.50 x 16.40 x 6.60 cm	33.50 x 16.40 x 6.60 cm	43.20 x 20.50 x 6.60 cm

**ATEN PSS PP v3.0 DVI Secure KVM Switches**

Function	CS1182D	CS1184D	CS1188D
<b>Computer Connections</b>	2	4	8
<b>Port Selection</b>	Pushbutton		
<b>Connectors</b>			
Console Ports	2 x USB Type-A Female (Black) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x DVI-I Dual Link Female (White) 1 x Mini Stereo Jack Female (Green; front panel)		2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x DVI-I Dual Link Female (White) 1 x Mini Stereo Jack Female (Green; front panel)
KVM Ports	4 x USB Type-B Female (White)	8 x USB Type-B Female (White)	16 x USB Type-B Female (White)
	2 x DVI-I Dual Link Female (White)	4 x DVI-I Dual Link Female (White)	8 x DVI-I Dual Link Female (White)
	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)	8 x Mini Stereo Jack Female (Green)
Power	1 x 3-prong AC Socket		
USB CAC Port	1 x USB Type-A Female (White; front panel)		
<b>Switches</b>			
Port Selection	2 x Pushbuttons	4 x Pushbuttons	8 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker		
<b>LEDs</b>			
On Line / Selected (KVM Port)	2 (Orange)	4 (Orange)	8 (Orange)
Online / Selected (CAC Port)	2 (Green)	4 (Green)	8 (Green)
Video	1 (Green)		
Key Lock	3 (Green)		
Power	1 (Blue)		
<b>Emulation</b>			
Keyboard / Mouse	USB		
Video	3840x2160@30Hz*; DVI Dual Link: 2560x1600; DVI Single Link: 1920x1200 DVI-A: 2048x1536		
Maximum Input Power Rating	100–240V~; 50-60 Hz; 1A		
Power Consumption	AC110V:4.4W AC220V:4.4W	AC110V:5.4W AC220V:5.4W	AC110V:8.3W AC220V:8.2W
<b>Environmental</b>			
Operating Temperature	0-50°C		
Storage Temperature	-20-60°C		
Humidity	0 - 80% RH, Non-condensing		
<b>Physical Properties</b>			
Housing	Metal		
Weight	1.78 kg	1.79 kg	3.05 kg
Dimensions (L x W x H)	33.50 x 16.40 x 4.40 cm	33.50 x 16.40 x 4.40 cm	43.20 x 20.50 x 6.60 cm

Note: \* DVI Secure KVM Switches offer 3840 x 2160 @ 30 Hz video output on compatible HDMI-interfaced monitors/computers with ATEN DVI-to-HDMI KVM cables.



**ATEN PSS PP v3.0 DVI Dual Display Secure KVM Switches**

Function	CS1142D	CS1144D	CS1148D
<b>Computer Connections</b>	2	4	8
<b>Port Selection</b>	Pushbutton		
<b>Connectors</b>			
Console Ports	2 x USB Type-A Female (Black) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 2 x DVI-I Dual Link Female (White) 1 x Mini Stereo Jack Female (Green; front panel)		2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 2 x DVI-I Dual Link Female (White) 1 x Mini Stereo Jack Female (Green; front panel)
KVM Ports	4 x USB Type-B Female (White)	8 x USB Type-B Female (White)	16 x USB Type-B Female (White)
	4 x DVI-I Dual Link Female (White)	8 x DVI-I Dual Link Female (White)	16 x DVI-I Dual Link Female (White)
	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)	8 x Mini Stereo Jack Female (Green)
Power	1 x 3-prong AC Socket		
USB CAC Port	1 x USB Type-A Female (White; front panel)		
<b>Switches</b>			
Port Selection	2 x Pushbuttons	4 x Pushbuttons	8 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker		
<b>LEDs</b>			
On Line / Selected (KVM Port)	2 (Orange)	4 (Orange)	8 (Orange)
Online / Selected (CAC Port)	2 (Green)	4 (Green)	8 (Green)
Video	2 (Green)		
Key Lock	3 (Green)		
Power	1 (Blue)		
Emulation	USB		
Keyboard / Mouse	USB		
Video	3840x2160@30Hz*; DVI Dual Link: 2560x1600; DVI Single Link: 1920x1200 DVI-A: 2048x1536		
Maximum Input Power Rating	100–240V~; 50-60 Hz; 1A		
Power Consumption	AC110V:5.8W AC220V:5.6W	AC110V:8.2W AC220V:7.8W	AC110V:17.6W AC220V:17.7W
<b>Environmental</b>			
Operating Temperature	0-50°C		
Storage Temperature	-20-60°C		
Humidity	0 - 80% RH, Non-condensing		
<b>Physical Properties</b>			
Housing	Metal		
Weight	2.12 kg	2.13 kg	3.35 kg
Dimensions (L x W x H)	33.50 x 16.40 x 6.60 cm	33.50 x 16.40 x 6.60 cm	43.20 x 20.50 x 6.60 cm

Note: \* DVI Secure KVM Switches offer 3840 x 2160 @ 30 Hz video output on compatible HDMI-interfaced monitors/computers with ATEN DVI-to-HDMI KVM cables.

Product information is subject to change without prior notice.

**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com

Publish Date: 04/2018 V1.0



© Copyright 2018 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.