

COURIER M2M 3G CELLULAR MODEM ACCESSORIES

CELLULAR
M2M

SIM Cards are available for AT&T, Rogers, and Vodafone networks around the world with optional SIM activation at time of shipment or manual activation via online portal access. Add additional mobile capabilities with a GPS antenna, a GSM Diversity Antenna, and a DC Cable that allows easy connection to automotive or other DC power sources. Add Ethernet capability to the USR3500 Cellular Modem with this Expansion Card to connect 10/100 Ethernet devices.


USRobotics®

A Division of UNICOM® Global

USR3506-ETH ETHERNET EXPANSION KIT

PACKAGE CONTENTS

- Ethernet Expansion Card
- Backplate and spring contacts
- RJ45 Interface Cable



FEATURES AND SERVICES

- IEEE 802.3 Compatible
- Integrated MAC and 10 BASE-T PHY
- Receiver and collision squelch circuit
- Supports one 10BASE-T port
- Supports Full and Half-Duplex modes
- Shielded RJ-45

USR3506-ACC MOBILE ACCESSORY KIT

PACKAGE CONTENTS

- DC Cable
- GPS Antenna
- GSM Antenna



USR3505-xxx SIM CARDS

ATT - AT&T, NORTH AMERICA
ROG - ROGERS, CANADA
VOD - VODAFONE, GLOBAL
ACT - ACTIVATION



DC Cable		
Length		1.5M
Terminations		10-pin Microfit female connector
		6-wires, 50mm length, stripped & tinned
		2@20AWG, 4@28AWG
Fuse		2A/250V slow blow, 5*20mm, replaceable
Diversity Antenna*		
Antenna Size [W x L x H]		18.4 x 8.0 x 49.5mm
Frequency Range supported [MHz]		850 / 900 / 1800 / 1900 / 2100
Connector		SMA (Male)
Max Gain [dBi]	824 - 960 MHz	1.0 (peak), -0.5 (min)
	1710 - 1990 MHz	2.0 (peak), 0.5 (min)
	1920 – 2170 MHz	2.5 (peak), 2.0 (min)
Efficiency [%] / [dB]	824 - 960 MHz	65 / -1.8 (peak), 50 / -3.0 (min)
	1710 - 1990 MHz	65 / -1.8 (peak), 50 / -3.0 (min)
	1920 – 2170 MHz	65 / -1.8 (peak), 50 / -3.0 (min)
Return loss min. [dB]	824 - 960 MHz	-4
	1710 - 1990 MHz	-6
	1920 – 2170 MHz	-6
Impedance		50Ω
Electrical Length		¼λ
Operating Temperature [°C]		-40 to +85

* Diversity Antenna specifications are typical and may vary.

GPS Antenna	
Weight	< 110 grams
Antenna Size	49x39x14mm
Cable	RG174/U 3 meters
Connector	MMCx m. right angle
Mounting	Magnetic base
Housing	Black
Center Frequency	1575.42MHz ± 3 MHz
V.S.W.R	1.5 : 1
Band Width	±5 MHz
Impedance	50Ω
Peak Gain	> 3dBic Based on 7x7cm ground plane
Gain Coverage	> -4dBic at -90° < 0 < +90° (over 75% Volume)
Polarization	RHCP
LNA Gain (without cable)	28dB (typical)
Noise Figure	1.5dB
Filter Out Band Attenuation (f0=1575.42 MHz)	7dB Min f0+/-20MHZ
	20dB Min f0+/-50MHZ
	30dB Min f0+/-100MHZ
V.S.W.R	< 2.0
DC Voltage	3.0V to 5.0V
DC Current	10mA Max
Operating Temp [°C]	-40 to +85
Weatherproof	100% Waterproof

USRobotics®

A Division of UNICOM® Global

www.usr.com

Copyright© 2014 U.S. Robotics Corporation, a Division of UNICOM Global. All rights reserved. U.S. Robotics, and USRobotics are registered trademarks of U.S. Robotics Corporation. Other brand names and product names are for identification purposes only and may be trademarks or registered trademarks of their respective companies.